



www.as-schwabe.de

STECKY

Combination units

Overview about all benefits :



Ergonomic handle offers an excellent catch, even with gloves

STECKY

Housing made of special plastic highly shock resistant



Powder-coated metal frame with edge protection

Cord made of heavy-duty rubber H07 RN-F from 5G1,5 up to 5G6

STECKY DUO

Stable metal foot with cable rewind



Velcro fastener for fixing the cord at the frame



Stecky DUO with phase display



Stecky Duo with 2 USB-Ports to recharge mobile phones, handlamp batteries and so on



STECKY




**STECKY
DUO**

STECKY

Combination unit

The STECKY range includes various combination units from 3,5 to 22 kW. Depending on the model, up to twelve outlets such as shock-proof sockets, USB-Ports or CEE sockets are available.

All models of the STECKY range are  for indoor and permanent outdoor use. Integrated protection devices avoid accidents.



Input / Plug



CEE plug
230 V, 16 A, 3-pole



CEE plug
400 V, 16 A, 5-pole



CEE plug
400 V, 32 A, 5-pole

Phase display



L1, L2, L3

Output / Socket



Shock-proof socket outlet
German standard
230 V, 16 A, 2PE



CEE socket
230 V, 16 A, 3-pole



CEE socket
400 V, 16 A, 5-pole



CEE socket
400 V, 32 A, 5-pole



2 USB-Ports
5 V / 2,1 A

Protection



FI/RCD

RCD 40 A / 30 mA, 4-pole, A type
RCBO 25 A / 30 mA, 2-pole, C curve, A type



C16A

MCB 16 A, 3-pole, C type
MCB 16 A, 1-pole, C type



STECKY

Combination units



STECKY 11



Input 16 A



CEE plug 400 V, 16 A, 5-pole

Output

4x Shock-proof socket outlet 230 V, 16 A, 2PE
2x CEE sockets 400 V, 16 A, 5-pole



STECKY 11+




Input 16 A



CEE plug 400 V, 16 A, 5-pole

Output

 Shock-proof socket outlet 230 V, 16 A, 2PE
2x CEE sockets 400 V, 16 A, 5-pole



STECKY 12



Input 32 A



CEE plug 400 V, 32 A, 5-pole

Output

4x Shock-proof socket outlet 230 V, 16 A, 2PE
1x CEE socket 400 V, 16 A, 5-pole
1x CEE socket 400 V, 32 A, 5-pole



STECKY 13



Input 32 A



CEE plug 400 V, 32 A, 5-pole

Output

4x Shock-proof socket outlet 230 V, 16 A, 2PE
1x CEE socket 400 V, 16 A, 5-pole
1x CEE socket 400 V, 32 A, 5-pole



STECKY 14



Input 16 A



CEE plug 230 V, 16 A, 3-pole

Output

4x Shock-proof socket outlets 230 V, 16 A, 2PE
2x CEE sockets 230 V, 16 A, 3-pole



Technical data

- Housing made of special plastic highly shock resistant
- Powder-coated metal frame with edge protection
- Ergonomic handle and cable rewind
- Dimensions: 230 x 417 x 220mm
- Tested according to DIN VDE 0620-1, ICE 60309, EN 61439-4, DIN EN 50525-2
- **IP44** splash proof
- Intended for indoor and permanent outdoor use



Cord	Protection	Output power	PU	EAN	Art.-No.
2,5 m H07RN-F 5G2,5	–	≈ 11 kW	1	4011160609602	60960

Cord	Protection	Output power	PU	EAN	Art.-No.
2,5 m H07RN-F 5G2,5	 FI/RCD 1x RCD 40 A / 30 mA, 4-pole, A type	≈ 11 kW	1	4011160609619	60961

Cord	Protection	Output power	PU	EAN	Art.-No.
4,5 m H07RN-F 5G4	 C16A 2 x MCB 16 A, 3-pole, C type 1 x MCB, 16 A, 1-pole, C type	≈ 22 kW	1	4011160609626	60962

Cord	Protection	Output power	PU	EAN	Art.-No.
4,5 m H07RN-F 5G4	 FI/RCD C16A 1x RCD 40 A / 30 mA, 4-pole, A type 1 x MCB, 16 A, 3-pole, C type 2 x MCB, 16 A, 1-pole, C type	≈ 22 kW	1	4011160609633	60963

Cord	Protection	Output power	PU	EAN	Art.-No.
2,5 m H07RN-F 3G2,5	–	≈ 3,5 kW	1	4011160608698	60869

STECKY DUO

Combination units



STECKY DUO 1

Input 16 A



CEE plug 400 V, 16 A, 5-pole

Output

8x Shock-proof socket outlet 230 V, 16 A, 2PE

4x CEE sockets 400 V, 16 A, 5-pole



STECKY DUO 2

Input 16 A



CEE plug 400 V, 16 A, 5-pole

Output

8x Shock-proof socket outlet 230 V, 16 A, 2PE

2x CEE sockets 400 V, 16 A, 5-pole

2x USB ports 5 V / 2,1 A

Phase display L1, L2, L3



STECKY DUO 3

Input 32 A



CEE plug 400 V, 32 A, 5-pole

Output

6x Shock-proof socket outlets 230 V, 16 A, 2PE

2x CEE sockets 400 V, 16 A, 5-pole

2x CEE sockets 400 V, 32 A, 5-pole

2x USB ports 5V / 2,1A

Phase display L1, L2, L3



STECKY DUO 4

Input 32 A



CEE plug 400 V, 32 A, 5-pole

Output

6x Shock-proof socket outlets 230 V, 16 A, 2PE

1x CEE socket 230 V, 16 A, 3-pole

1x CEE socket 400 V, 16 A, 5-pole

2x CEE sockets 400 V, 32 A, 5-pole

2x USB ports 5 V / 2,1 A

Phase display L1, L2, L3



STECKY DUO 5

Input 16 A



CEE plug 230 V, 16 A, 3-pole

Output

7x Shock-proof socket outlet 230 V, 16 A, 2PE

4x CEE sockets 230 V, 16 A, 3-pole

2x USB ports 5 V / 2,1 A



Technical data

- Housing made of special plastic highly shock resistant
- Powder-coated metal frame with edge protection
- Ergonomic handle and cable rewind
- Dimensions: 230x417x220mm
- Tested according to DIN VDE 0620-1, ICE 60309, EN 61439-4, DIN EN 50525-2
- **IP44** splash proof
- Intended for indoor and permanent outdoor use.



Cord	Protection	Output power	PU	EAN	Art.-No.
3,4 m H07RN-F 5G2,5	 1x RCD 40 A / 30 mA, 4-pole, A type	≈ 11 kW	1	4011160609312	60931
3,4 m H07RN-F 5G2,5	 1x RCD 40 A / 30 mA, 4-pole, A type	≈ 11 kW	1	4011160609329	60932
2,1 m H07RN-F 5G6	 1x RCD 40 A / 30 mA, 4-pole, A type 1 x MCB 16 A, 3-pole, C type 3 x MCB 16 A, 1-pole, C type	≈ 22 kW	1	4011160609336	60933
3,4 m H07RN-F 5G6	 1x RCD 40 A / 30 mA, 4-pole, A type 1 x MCB 16 A, 3-pole, C type 4 x MCB 16 A, 1-pole, C type	≈ 22 kW	1	4011160609343	60934
3,4 m H07RN-F 3G2,5	 1 x RCD 15 A / 30 mA, 2-pole, C curve, A type	≈ 3,5 kW	1	4011160609350	60935



STECKY



STECKY DUO



STECKY

Combination units

The right model for every application:

- ☑ Combination units from 3,5 to 22 kW.
6 sockets up to 12 sockets available
- ☑ **Stable construction** for optimal use at construction sites, fairs, campsites ...
- ☑ **Weatherproof and safe**
- ☑ **RCD / MCB protecting devices**
- ☑ **Comfortable handling by a huge handle**
- ☑ **USB-port** to recharge mobile phones, handlamp batteries and so on

 All rights reserved. Reproduction only with authorization of as - Schwabe GmbH, 11/2019

Your partner for professional lighting and electrical products

as - Schwabe GmbH
Merkurstraße 10
D - 72184 Eutingen

Tel. +49 7457 9 48 53 10
Fax +49 7457 9 48 53 30

www.as-schwabe.de
d.mueck@as-schwabe.de

as[®]
Schwabe
TechnikProdukte