

KN DB 1410 / 1316

Terminal for NH-fuse switch disconnectors


Product-Information

Terminal for NH-fuse switch disconnectors KN DB 1410 and KN DB 1316


- solid terminal for NH-fuse switch disconnectors
- compact measurements
- improved pull-off saveness through double screwing of connection leads
- mounting hole M8
- Standard screw of the fuse disconnectors can be used (a replacement of the screws is not necessary)

Technical data

maximum operating voltage	690V AC	
	1500V DC	
maximum operating current	250A	
cross section	KN DB 1410	KN DB 1316
	4 x 10 mm ²	1 x 16 + 2 x 25 mm ²
U-single wire, R-multi wire	4 x 2,5 - 10 mm ²	1 x 2,5 - 16 mm ²
		2 x 2,5 - 25 mm ²
K-fine wire (with sleeve)	4 x 2,5 - 6 mm ²	1 x 2,5 - 10 mm ²
F-fine wire (with sleeve)		2 x 2,5 - 16 mm ²
maximum torque	2 Nm	
pin length	18mm	
pin width x pin thickness	21,5 x 4 mm	
diameter mounting hole	8,5 mm (M8)	
material	brass, blank	



KN DB 1410



KN DB 1316

article-no.	no. of terminals	package qty.
KN DB 1410	4	25 pcs.
KN DB 1316	3	25 pcs.